



CONNECTIONS					
MEDIUM	PRESSURE	TEMP	CONNECT	MIN. FLOW	ADVISED FLOW
compr. air, dry, oil free, filtered 3 µm	600kPa		G 1/2"	160 n.m3/h	
cold water	min 300 kPa	10 °C	G 3/4"	35 L/min	100 L/min
warm water	min 300 kPa	60 °C	G 3/4"	35 L/min	100 L/min
drain	0 kPa	10-89 °C	dia 76 mm		

ELECTRICAL CONNECTIONS		
max. requested power	16	Kw
voltage	see type plate machine	
cycle	see type plate machine	
connection	3 phase + Pe	
simultaneously value	100	%
T-base10 connection for ethernet	direct connection RJ45 plug	

MISCELLANEOUS		
WEIGHT	550	Kg
SOUND	≤ 80	Db(A)
WATER QUALITY	EG 98/83	
HARDNESS	< 20	"DH (350mg CaCO3/liter)
CONDUCTIVITY	>250 and < 2000	PPbµS/cm
IRON	< 200	PPB
SILICATE	< 5	PPM
CHLORIDE	< 50	PPM

Titel 03 TRP 700 - spare parts version 2.0				indien geen tolerantie is opgegeven, geldt: ±0,5		Project 	
Klant	Schaal	Datum 6-10-2011	Formaat A2	Getekend Toon	Gecontr.	Gewicht N/A	
Project no.	A	C			E		
Artikel no.	B	D			F		
 Elpress Cleaning Systems Handelstraat 21 5831 AV Boxmeer tel. : 0485-550490 fax. : 0485-514022 mail: info@elpress.nl www.elpress.nl				Tekening nr. 0909001950		Rev. E	
				DEZE TEKENING IS EIGENDOM VAN ELPRESS BV. HET IS EEN VERTROUWELIJK DOCUMENT EN MAG NIET GECOPIERD, GEBRUIKT OF OPENBAAR GEMAAKT WORDEN ZONDER SCHRIFTELIJKE TOESTEMMING.			

84333_00-ENG